



This product is for the professional painting of vehicles  
only after reference to the manufacturer's data sheet.



## SAFETY DATA SHEET

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Hidrobase Azul (verde) transparente HI223S

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Car and vehicle refinishing

Uses advised against
For professional use only.

Not applicable.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer** : HELLA, S.A.  
Avda. de los Artesanos 24  
28760 Tres Cantos - Madrid  
Tif.: +34 91 806 19 00  
Fax.: +34 91 803 81 30  
www.hella.es

**e-mail address of person responsible for this SDS** : asistente.quimica@hella.es

#### 1.4 Emergency telephone number

##### National advisory body/Poison Centre

**Telephone number** : Tif.: +34 91 562 04 20

##### Supplier

**Telephone number** : Tif.: +34 91 806 19 00 (de 08.00 a 16.30 hrs)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302  
Acute Tox. 4, H312  
Acute Tox. 4, H332

**Ingredients of unknown toxicity** : Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 90.9%

**Ingredients of unknown ecotoxicity** : Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 88.1%

##### Classification according to Directive 1999/45/EC [DPD]

##### Europe

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

## SECTION 2: Hazards identification

**Classification** : Not classified.

### Denmark

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : Not classified.

### Norway

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : Not classified.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : Harmful if swallowed, in contact with skin or if inhaled.

### Precautionary statements

**Prevention** : Wear protective gloves. Wear protective clothing. Avoid breathing vapour.

**Response** : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Europe

**Hazardous ingredients** : 2-butoxyethanol  
2-dimethylaminoethanol

### Denmark

**Hazardous ingredients** : 2-butoxyethanol  
2-dimethylaminoethanol

### Norway

**Hazardous ingredients** : 2-butoxyethanol  
2-dimethylaminoethanol

**Supplemental label elements** : Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and triisobutyl phosphate. May produce an allergic reaction.

**Supplemental label elements** : Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and triisobutyl phosphate. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

## SECTION 2: Hazards identification

### 2.3 Other hazards

Other hazards which do not result in classification : None known.

## SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
<b>Europe</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.	Aquatic Chronic 4, H413	[1]
2-dimethylaminoethanol	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Austria</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.	Aquatic Chronic 4, H413	[1]
2-dimethylaminoethanol	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1] [2]
	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

**SECTION 3: Composition/information on ingredients**

				<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Belgium</b>						
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38		Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5  <1	Not classified.  R43		  Skin Sens. 1, H317	[1]  [1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34		Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
				<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Bulgaria</b>						
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38		Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5  <1	Not classified.  R43		  Skin Sens. 1, H317	[1]  [1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34		Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]



**SECTION 3: Composition/information on ingredients**

<b>Denmark</b>						
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.			[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43			[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34			[1]
<b>Estonia</b>						
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.			[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43			[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34			[1]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Finland</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>France</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]



**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Germany</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1] [2]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Greece</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]



**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Hungary</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Ireland</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1] [2]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Italy</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Latvia</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Lithuania</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Netherlands</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Norway</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Poland</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Portugal</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
<b>Romania</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1] [2]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Slovakia</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Slovenia</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Spain</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	
<b>Sweden</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8  EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	>=1, <5	Not classified.		[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	R43	Skin Sens. 1, H317	[1]
		>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]



**SECTION 3: Composition/information on ingredients**

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>Switzerland</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.	Aquatic Chronic 4, H413	[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]
<b>Turkey</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.	Aquatic Chronic 4, H413	[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

### SECTION 3: Composition/information on ingredients

			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	
<b>United Kingdom (UK)</b>					
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	>=7, <10	Xn; R20/21/22 Xi; R36/38	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 4, H413	[1] [2]
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper triisobutyl phosphate	EC: 205-685-1 CAS: 147-14-8	>=1, <5	Not classified.		[1]
	EC: 204-798-3 CAS: 126-71-6 Index: Selfclassified	<1	R43	Skin Sens. 1, H317	[1] [2]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	>=0.1, <1	R10 Xn; R20/21/22 C; R34	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

## SECTION 4: First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains triisobutyl phosphate. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and materials for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling** : Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

#### Recommendations

: Not available.

#### Industrial sector specific solutions

: Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
<b>Europe</b> 2-butoxyethanol	<b>EU OEL (Europe, 12/2009). Absorbed through skin.</b> STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes. TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
<b>Austria</b> 2-butoxyethanol	<b>GKV_MAK (Austria, 12/2011). Absorbed through skin.</b> PEAK: 200 mg/m <sup>3</sup> , 4 times per shift, 30 minutes. PEAK: 40 ppm, 4 times per shift, 30 minutes. TWA: 98 mg/m <sup>3</sup> , 4 times per shift, 8 hours. TWA: 20 ppm, 4 times per shift, 8 hours.
triisobutyl phosphate	<b>GKV_MAK (Austria, 12/2011).</b> CEIL: 100 mg/m <sup>3</sup> , 3 times per shift, 60 minutes. TWA: 50 mg/m <sup>3</sup> 8 hours.
<b>Belgium</b> 2-butoxyethanol	<b>Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). Absorbed through skin.</b> STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes. TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
<b>Bulgaria</b> 2-butoxyethanol	<b>България Министерство на труда и социалната политика и Министерството на здравеопазването (Bulgaria, 1/2012). Absorbed through skin.</b> Limit value 15 min: 246 mg/m <sup>3</sup> 15 minutes. Limit value 8 hours: 98 mg/m <sup>3</sup> 8 hours. Limit value 15 min: 50 ppm 15 minutes. Limit value 8 hours: 20 ppm 8 hours.
<b>Croatia</b>	

**SECTION 8: Exposure controls/personal protection**

2-butoxyethanol	<b>MinGoRP GVI/KGVI (Croatia, 1/2009). Absorbed through skin.</b> STELV: 246 mg/m <sup>3</sup> 15 minutes. STELV: 50 ppm 15 minutes. ELV: 98 mg/m <sup>3</sup> 8 hours. ELV: 20 ppm 8 hours.
triisobutyl phosphate	<b>MinGoRP GVI/KGVI (Croatia, 1/2009).</b> STELV: 5 mg/m <sup>3</sup> 15 minutes. ELV: 5 mg/m <sup>3</sup> 8 hours.
2-dimethylaminoethanol	<b>MinGoRP GVI/KGVI (Croatia, 1/2009).</b> STELV: 22 mg/m <sup>3</sup> 15 minutes. STELV: 6 ppm 15 minutes. ELV: 7.4 mg/m <sup>3</sup> 8 hours. ELV: 2 ppm 8 hours.
<b>Czech Republic</b>	
2-butoxyethanol	<b>MZCR PEL/NPK-P (Czech Republic, 2/2012). Absorbed through skin.</b> STEL: 200 mg/m <sup>3</sup> 15 minutes. STEL: 41.4 ppm 15 minutes. TWA: 100 mg/m <sup>3</sup> 8 hours. TWA: 20.7 ppm 8 hours.
<b>Denmark</b>	
2-butoxyethanol	<b>Arbejdstilsynet (Denmark, 10/2012). Absorbed through skin.</b> TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
<b>Estonia</b>	
2-butoxyethanol	<b>Sotsiaalminister (Estonia, 10/2007). Absorbed through skin. Skin sensitiser.</b> STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes. TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
<b>Finland</b>	
2-butoxyethanol	<b>Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 12/2011). Absorbed through skin.</b> STEL: 250 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes. TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
<b>France</b>	
2-butoxyethanol	<b>Ministère du travail (France, 7/2012). Absorbed through skin.</b> STEL: 246 mg/m <sup>3</sup> 15 minutes. Form: Risk for sensitisation STEL: 50 ppm 15 minutes. Form: Risk for sensitisation TWA: 49 mg/m <sup>3</sup> 8 hours. Form: Risk for sensitisation TWA: 10 ppm 8 hours. Form: Risk for sensitisation
<b>Germany</b>	
2-butoxyethanol	<b>TRGS900 AGW (Germany, 9/2012). Absorbed through skin.</b> PEAK: 196 mg/m <sup>3</sup> 15 minutes. PEAK: 40 ppm 15 minutes. TWA: 49 mg/m <sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.
triisobutyl phosphate	<b>TRGS900 AGW (Germany, 9/2012). Skin sensitiser.</b> TWA: 50 mg/m <sup>3</sup> 8 hours. PEAK: 100 mg/m <sup>3</sup> 15 minutes.
<b>Greece</b>	



**SECTION 8: Exposure controls/personal protection**

2-butoxyethanol	Υπουργείο Εργασίας και Κοινωνικών Υποθέσεων (Greece, 2/2012). Absorbed through skin. TWA: 120 mg/m <sup>3</sup> 8 hours. TWA: 25 ppm 8 hours.
<b>Hungary</b> 2-butoxyethanol	<b>25/2000. (IX. 30.) EüM-SzCsM együttes rendelet (Hungary, 12/2011). Absorbed through skin. Skin sensitiser.</b> PEAK: 246 mg/m <sup>3</sup> 15 minutes. TWA: 98 mg/m <sup>3</sup> 8 hours.
<b>Ireland</b> 2-butoxyethanol	<b>NAOSH (Ireland, 5/2010). Absorbed through skin.</b> OELV-15min: 246 mg/m <sup>3</sup> 15 minutes. OELV-15min: 50 ppm 15 minutes. OELV-8hr: 98 mg/m <sup>3</sup> 8 hours. OELV-8hr: 20 ppm 8 hours.
triisobutyl phosphate	<b>NAOSH (Ireland, 5/2010).</b> OELV-15min: 5 mg/m <sup>3</sup> 15 minutes. OELV-8hr: 5 mg/m <sup>3</sup> 8 hours.
<b>Italy</b> 2-butoxyethanol	<b>Ministero della Salute (Italy, 8/2009). Absorbed through skin.</b> Short Term: 246 mg/m <sup>3</sup> 15 minutes. Short Term: 50 ppm 15 minutes. 8 hours: 98 mg/m <sup>3</sup> 8 hours. 8 hours: 20 ppm 8 hours.
<b>Latvia</b> 2-butoxyethanol	<b>Ministru kabineta - AER (Latvia, 2/2011). Absorbed through skin.</b> STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes. TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.
2-dimethylaminoethanol	<b>Ministru kabineta - AER (Latvia, 2/2011).</b> TWA: 5 mg/m <sup>3</sup> 8 hours.
<b>Lithuania</b> 2-butoxyethanol	<b>Lietuvos Higienos Normos HN 23 (Lithuania, 10/2007). Absorbed through skin.</b> STEL: 100 mg/m <sup>3</sup> 15 minutes. STEL: 20 ppm 15 minutes. TWA: 10 ppm 8 hours. TWA: 50 mg/m <sup>3</sup> 8 hours.
<b>Netherlands</b> 2-butoxyethanol	<b>MinSZW Wettelijke Grenswaarden (Netherlands, 6/2011). Absorbed through skin.</b> STEL, 15-min ref: 246 mg/m <sup>3</sup> 15 minutes. OEL, 8-h TWA: 100 mg/m <sup>3</sup> 8 hours.
<b>Norway</b> 2-butoxyethanol	<b>Arbeidstilsynet (Norway, 12/2011). Absorbed through skin.</b> TWA: 50 mg/m <sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.
triisobutyl phosphate	<b>Arbeidstilsynet (Norway, 12/2011).</b> TWA: 0.2 ppm 8 hours. TWA: 2.5 mg/m <sup>3</sup> 8 hours.
<b>Poland</b>	



**SECTION 8: Exposure controls/personal protection**

2-butoxyethanol

**Rozporządzenie Ministra Pracy i Polityki Społecznej (Dz. U. 2002 Nr 217, poz. 1833, z późn. zm.) (Poland, 12/2011).**

STEL: 200 mg/m<sup>3</sup> 15 minutes.

TWA: 98 mg/m<sup>3</sup> 8 hours.

**Portugal**

2-butoxyethanol

**Instituto Português da Qualidade (Portugal, 3/2007).**

TWA: 20 ppm 8 hours.

**Romania**

2-butoxyethanol

**Ministerul Muncii, Familiei si Protectiei Sociale și Ministerul Sănătății (Romania, 1/2012). Absorbed through skin.**

Short term: 246 mg/m<sup>3</sup> 15 minutes.

Short term: 50 ppm 15 minutes.

VLA: 98 mg/m<sup>3</sup> 8 hours.

VLA: 20 ppm 8 hours.

triisobutyl phosphate

**Ministerul Muncii, Familiei si Protectiei Sociale și Ministerul Sănătății (Romania, 1/2012).**

Short term: 5 mg/m<sup>3</sup> 15 minutes.

VLA: 2 mg/m<sup>3</sup> 8 hours.

**Slovakia**

2-butoxyethanol

**Nariadenie Vlády Slovenskej republiky (Slovakia, 12/2011).**

**Absorbed through skin.**

STEL: 246 mg/m<sup>3</sup> 15 minutes.

TWA: 98 mg/m<sup>3</sup> 8 hours.

TWA: 20 ppm 8 hours.

STEL: 50 ppm 15 minutes.

**Slovenia**

2-butoxyethanol

**Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Slovenia, 12/2010).**

**Absorbed through skin.**

TWA: 98 mg/m<sup>3</sup> 8 hours.

TWA: 20 ppm 8 hours.

KTV: 245 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.

KTV: 50 ppm, 4 times per shift, 15 minutes.

**Spain**

2-butoxyethanol

**INSHT (Spain, 1/2012). Absorbed through skin.**

STEL: 245 mg/m<sup>3</sup> 15 minutes.

STEL: 50 ppm 15 minutes.

TWA: 98 mg/m<sup>3</sup> 8 hours.

TWA: 20 ppm 8 hours.

**Sweden**

2-butoxyethanol

**AFS 2011:18 (Sweden, 12/2011). Absorbed through skin.**

STEL: 100 mg/m<sup>3</sup> 15 minutes.

STEL: 20 ppm 15 minutes.

TWA: 50 mg/m<sup>3</sup> 8 hours.

TWA: 10 ppm 8 hours.

**Switzerland**

2-butoxyethanol

**SUVA (Switzerland, 1/2012). Absorbed through skin.**

STEL: 98 mg/m<sup>3</sup> 15 minutes.

STEL: 20 ppm 15 minutes.

TWA: 49 mg/m<sup>3</sup> 8 hours.

TWA: 10 ppm 8 hours.

**Turkey**

**SECTION 8: Exposure controls/personal protection**

2-butoxyethanol	<b>TR ISGGM OEL (Turkey, 3/2008). Absorbed through skin.</b> TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours. STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes.
<b>United Kingdom (UK)</b>	
2-butoxyethanol	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours.
triisobutyl phosphate	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 5 mg/m <sup>3</sup> 15 minutes. TWA: 5 mg/m <sup>3</sup> 8 hours.
2-dimethylaminoethanol	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 22 mg/m <sup>3</sup> 15 minutes. STEL: 6 ppm 15 minutes. TWA: 7.4 mg/m <sup>3</sup> 8 hours. TWA: 2 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

No DNELs/DMELs available.

**PNECs**

No PNECs available

**8.2 Exposure controls**

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

**Skin protection**

**Hand protection**

## SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber, Viton®, nitrile rubber

May be used: polyvinyl alcohol (PVA)

Not recommended: natural rubber (latex)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Best Practice Guideline 5 "Safe Use of Gloves" (June 2010) published by the European Solvents Industry Group (ESIG), available at <http://www.esig.org/en/library/publications/best-practice-guides>

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Recommended mask** :



P1A1

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Product Specific Information
- Odour** : Characteristic.
- Odour threshold** : Not available.
- pH** : Neutral.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : 100°C

**SECTION 9: Physical and chemical properties**

Flash point	: Closed cup: 101°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Burning time	: Not applicable.
Burning rate	: Not applicable.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 1.015
Solubility(ies)	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 3.940072 cm <sup>2</sup> /s
Explosive properties	: Not available.
Oxidising properties	: Not available.

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with

## SECTION 11: Toxicological information

the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains triisobutyl phosphate. May produce an allergic reaction.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
triisobutyl phosphate	LD50 Oral	Rat	>5 g/kg	-
2-dimethylaminoethanol	LD50 Oral	Rat	2 g/kg	-

**Conclusion/Summary** : Not available.

### Acute toxicity estimates

Route	ATE value
Oral	611.1 mg/kg
Dermal	1344.3 mg/kg
Inhalation (vapours)	11.61 mg/l

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
triisobutyl phosphate	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Skin - Moderate irritant	Rabbit	-	500 microliters	-
2-dimethylaminoethanol	Eyes - Severe irritant	Rabbit	-	5 microliters	-
	Skin - Mild irritant	Rabbit	-	445 milligrams	-

**Conclusion/Summary** : Not available.

### Sensitisation

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-dimethylaminoethanol	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

**SECTION 11: Toxicological information**

Not available.

**Other information** : Not available.**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1000 mg/l Marine water	Crustaceans - Chaetogammarus marinus - Young	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours

**Conclusion/Summary** : Not available.**12.2 Persistence and degradability****Conclusion/Summary** : Not available.**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-butoxyethanol	0.83	-	low
29H,31H-phthalocyaninato (2-)-N29,N30,N31,N32 copper	6.6	-	high
2-dimethylaminoethanol	-0.55	-	low

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment****PBT** : Not applicable.**vPvB** : Not applicable.**12.6 Other adverse effects** : No known significant effects or critical hazards.**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

## SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
	waste paint and varnish containing organic solvents or other dangerous substances

### Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Not emptied containers are hazardous waste.

Type of packaging	European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10* packaging containing residues of or contaminated by dangerous substances

- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	Not regulated.	Not regulated.	Not regulated.
<b>Transport hazard class(es)</b>	Not regulated.	Not regulated.	Not regulated.
<b>Packing group</b>	-	-	-
<b>Environmental hazards</b>	No.	No.	No.
<b>Additional information</b>	-	-	-



## SECTION 14: Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

##### Other EU regulations

**VOC for Ready-for-Use Mixture** : Not applicable.

**Europe inventory** : All components are listed or exempted.

**Priority List Chemicals (793/93/EEC)** : Listed

##### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

##### Austria

**Limitation of the use of organic solvents** : Permitted.

##### Czech Republic

**Storage code** : IV

##### Denmark

**MAL-code** : 1-3

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

**SECTION 15: Regulatory information**

MAL-code: 1-3

**Application:** When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone.

- Coveralls must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask and coveralls must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.- Full mask with combined filter, arm protectors and apron must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order on young people's dangerous work.

**List of undesirable substances** : Listed

Finland

**NACE** : Not available.

**UC62** : Not available.

France

**Social Security Code, Articles L 461-1 to L 461-7** : 2-butoxyethanol RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

**Storage code** : 10

**Hazard class for water** : 1 Appendix No. 4

**Technical instruction on air quality control** : TA-Luft Number 5.2.5: 8.3%  
TA-Luft Class III - Number 5.2.2: 2.8%

## SECTION 15: Regulatory information

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not classified.

### Netherlands

**Water Discharge Policy (ABM)** : Slightly harmful to aquatic organisms. Abatement effort: B

### Norway

### Portugal

Product/ingredient name	List name	Name on list	Classification	Notes
2-butoxyethanol	Portugal Occupational Exposure Limits	2-butoxietanol; EGBE	Carc. A3	-

### Switzerland

**VOC content** : VOC (w/w): 7.44508126152%

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

**CEPE code** : 2

**OAR group** : **OAR group:** 2  
Not applicable.

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H312	Calculation method
Acute Tox. 4, H332	Calculation method

### Europe

**Full text of abbreviated H statements** :

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H413 May cause long lasting harmful effects to aquatic life.

## SECTION 16: Other information

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

### Austria

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

### Belgium

**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R34- Causes burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact.
<b>Full text of classifications [DSD/DPD]</b>	: C - Corrosive Xn - Harmful Xi - Irritant
<b><u>Bulgaria</u></b>	
<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

## SECTION 16: Other information

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

### Croatia

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

### Czech Republic

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.



**SECTION 16: Other information**

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

**Denmark**

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

**Estonia**



**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R34- Causes burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact.
<b>Full text of classifications [DSD/DPD]</b>	: C - Corrosive Xn - Harmful Xi - Irritant
<b><u>Finland</u></b>	
<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

## SECTION 16: Other information

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

### France

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

### Germany

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.

**SECTION 16: Other information**

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

Greece

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

Hungary

**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R34- Causes burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact.
<b>Full text of classifications [DSD/DPD]</b>	: C - Corrosive Xn - Harmful Xi - Irritant
<b>Ireland</b>	
<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**SECTION 16: Other information**

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

Italy

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

Latvia

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.



**SECTION 16: Other information**

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

Lithuania

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

Netherlands

**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R34- Causes burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact.
<b>Full text of classifications [DSD/DPD]</b>	: C - Corrosive Xn - Harmful Xi - Irritant
<b>Norway</b>	
<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3



**SECTION 16: Other information**

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

**Poland**

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

**Portugal**

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

## SECTION 16: Other information

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

### Romania

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

### Slovakia

## SECTION 16: Other information

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R34- Causes burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact.
<b>Full text of classifications [DSD/DPD]</b>	: C - Corrosive Xn - Harmful Xi - Irritant
<b>Slovenia</b>	
<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**SECTION 16: Other information**

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

Spain

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
Xn - Harmful  
Xi - Irritant

Sweden

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H413 May cause long lasting harmful effects to aquatic life.

**SECTION 16: Other information**

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

Switzerland

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

Turkey



**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R34- Causes burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact.
<b>Full text of classifications [DSD/DPD]</b>	: C - Corrosive Xn - Harmful Xi - Irritant
<b><u>United Kingdom (UK)</u></b>	
<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 4, H413 LONG-TERM AQUATIC HAZARD - Category 4 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

**SECTION 16: Other information**

**Full text of abbreviated R phrases** : R10- Flammable.  
 R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
 R34- Causes burns.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : C - Corrosive  
 Xn - Harmful  
 Xi - Irritant

**Date of printing** : 3/24/2014.

**Date of issue/ Date of revision** : 3/24/2014.

**Date of previous issue** : No previous validation.

**Version** : 1

Notice to reader

**FOR PROFESSIONAL USE ONLY**

**IMPORTANT NOTE** *The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.*

*Brand names mentioned in this data sheet are trademarks of or are licensed to HELLA. Head Office HELLA, S.A., Avda. de los Artesanos 24, 28760 Tres Cantos - Madrid, Tlf.: +34 91 806 19 00, Fax.: +34 91 803 81 30, www.HELLA.eswww.hella.es*